

Appln. No. 10/612,423

Attorney Docket No. 10541-1736

**I. Amendments to the Specification**

Please replace paragraph 0017 with the following amended paragraph:

[0017] The aiming screw 28 includes a threaded middle section 82 that is received within a threaded bore 84 defined in a boss 86 of the housing 22. The aiming screw 28 may be provided with a self-tapping screw thread such that the threaded bore is formed in the boss 86 when the screw 28 is installed. The first end or the upper end 83 of the aiming screw 28 is formed with a driving head 88 suitably shaped to receive a driving tool (not shown) for imparting rotation to the aiming screw 28. The opposing or second end 85 of the screw 28 is provided with a generally round or ball head 92. The aiming screw 28, threaded boss 86 and channel 70 of the adjustment clip 64 are all oriented such that when fully assembled, the driving head 88 of the aiming screw 28 extends generally vertically through the top wall 73 of the housing 22, while the ball head 92 is received within the channel 70.

Please replace paragraph 0018 with the following amended paragraph:

[0018] For ease of assembly, the diameter "d" of the ball head 92 is less than the diameter "D" of the threaded bore 84. As such the ball head 92 can be inserted through the threaded bore 84 as the aiming screw 28 is mounted therein via the threaded middle section 82.